

M300CORPUS3G030211

Having launched the first mid-wheel drive platform to the wheelchair market nearly 30 years ago, Permobil honors that rich tradition with the addition of the M300 to its product line. Developed by Permobil Senior Designers, Mehdi Mirzaie and Bo Engman, the M300 features the ground-breaking, patent-pending Climbing and Traction Link system. With its compact size, the M300 has a tight 20" turning radius, comes with PG 120 amp R-Net electronics and offers two speed packages—6 MPH standard and 7.5 MPH optional. The M300 also features stylish easy-to-replace swing arms covers made of scratch resistant material, which protect the swing arms from unsightly chips and scrapes. Easy to maintain, the M300 provides

M300
CORPUS 3G

quick access to components and requires no special tools for servicing



CATLINK SUSPENSION

Casters are connected for added climbing stability.

ADVANCED SHOCK DESIGN

Easily adjusted to provide a comfortable ride for any user.

TIGHT TURNING RADIUS

20" / 510 mm turning radius for increased maneuverability.

FRONT AND REAR TIE-DOWNS

Safety is first both in and out of the vehicle!

















AVAILABLE SHROUD COLORS





DIGITAL ARMY CAMO





REALTREE AP CAMO



AVAILABLE SHROUD COLORS

| Maximum User Weight | 300 lbs | 136 kg | | |
|--|--------------------|------------------|--|--|
| Maximum Speed Options | 6 MPH, 7.5 MPH | 10 km/h, 12 km/h | | |
| Driving Range ¹ | 13 miles | 21 km | | |
| Base Width | 24" | 615 mm | | |
| Base Length | 36.5" | 925 mm | | |
| Minimum Turning Radius | 20″ | 510 mm | | |
| Ground Clearance | 3″ | 75 mm | | |
| Optional Seat Elevator | 8″ | 200 mm | | |
| Battery Type | Group 24, Group 34 | | | |
| Drive Electronics | 120A R-net | | | |
| Maximum Slope ² | 9° Up / 9° Down | | | |
| LACTUAL DRIVING PANICE WILL VARY BASED ON DRIVING AND RATTERY CONDITIONS | | | | |

I ACTUAL DRIVING RANGE WILL VARY BASED ON DRIVING AND BATTERY CONDITIONS. 2 REFER TO OWNER MANUAL FOR SAFE DRIVING PRACTICES

| Seat to Floor Height | (Elevator) | 17.5" | 445 mm |
|---------------------------|-------------|--------------------|-----------------------|
| | (Seat Tube) | 17.5", 18.25", 19" | 445, 465, 485 mm |
| Tilt Options | (Power) | 0° – 50° | |
| | (Power) | -5° – 45° | |
| Recline Options | (Power) | 85° – 175° | |
| | (Manual) | 85° – 120° | |
| Legrest Elevation Options | (Power) | 85° – 170° | |
| | (Manual) | 85° – 170° | |
| Armrest Pad Lengths | | 10", 13", 16" | 260, 335, 410 mm |
| Seat Widths | | 17", 19", 21", 23" | 420, 470, 520, 570 mm |
| Seat Depths | | 14" - 22" | 370 — 570 mm |
| Backrest Heights | | 20", 23" – 28" | 500, 570 – 710 mm |